

#### TEST RESULT SUMMARY

The sample in the trademark of "weber.color power" was submitted by the Saint-Gobain weber Co.,Ltd. The series of test and test methods were conducted on December 2, 2011 in accordance with European Norms (EN 13888: 2009) with details as follows:

### Specification of cementitious grouts (CG)

Fundamental Characteristics							
Characteristics	Requirement	Test Method	Results				
Flexural strength after dry storage	≥ 2.5 N/mm <sup>2</sup>	EN 12808-3	PASS				
Compressive strength after dry storage	≥ 15 N/mm <sup>2</sup>	EN 12808-3	PASS				
Shrinkage	≤ 3 mm/m	EN 12808-4	PASS				
Water absorption after 30 min	≤ 5 g	EN 12808-5	PASS				
Water absorption after 240 min	≤ 10 g	EN 12808-5	PASS				

Regarding to the testing results, it was found that the properties of "weber.color power" are conformed to European Norms (EN 13888: 2009) test methods as specified. These results certify the adequacy and representative character of test samples only.

(Assoc. Prof. Dr. Veerasak Likhitruangsilp)

On Behalf of Head of Civil Engineering Department

lested by:

(Dr. Boarchai Comatneam



## FACULTY OF ENGINEERING

#### CHULALONGKORN UNIVERSITY

Type of test

FLEXURAL STRENGTH TEST (EN 12808-3)

Test specimen

Three (3) specimens in prism shape were cast in the laboratory.

The mix proporting of water to "weber.color power" ratio was 33% by weight.

Client

SAINT-GOBAIN WEBER CO., LTD.

Date of test

December 2, 2011

Test method

After mixing them thoroughly, the specimen was cast in the standard molds having a size of 40x40x160 mm.

The specimens are cured for 24 hours in molds, then stripped and cured in standard condition until conducting the test.

Test results

The flexural strength of specimens at the age of 28 days are shown as follows.

(The test results are good only for those specimens tested.)

,	no too too me generally and a second a second and a second a second and a second a second and a second and a second and a						
Specimen	Width of	Thickness of	Length of	Maximum Load	Flexural		
No.	Specimen, B	Specimen, D	Specimen	P	Strength	Remarks	
	(cm)	(cm)	(cm)	(kgf)	(ksc)		
ĩ	4.05	4.02	16.00	278	63.7	The flexural strength, Sf=3 P1/(2 BD <sup>2</sup> )	
2	4.06	4.05	16.00	294	66.2	where I (span length) is 10 cm.	
3	4.03	4.02	16.00	200	46.1	1 kgf/cm2 = 0.0981 N/mm2	
				Average	58.7	Average flexural strength = 5.76 N/mm2	

Note: This resutls certify the adequacy and representative character of the test samples only.

(Assoc. Prof. Dr. Veerasak Likhitruangsilp)

On Behalf of Head of Civil Engineering Department

(Dr. Boonchai Sangpetngam)



Type of test:

COMPRESSIVE STRENGTH TEST (EN 12808-3)

Test specimen:

Three (3) specimens in prism shape were cast in the laboratory.

The mix proporting of water to "weber.color power" ratio was 33% by weight.

Client:

SAINT-GOBAIN WEBER CO., LTD.

Date of test:

December 2, 2011

Test method:

After flexural test, the halves broken specimens were keeped in standard condition until conducting the compression test.

Test results:

The compressive strength of speimens at the age of 28 days are shown as follows.

(The test results are good only for those specimens tested.)

Specimen	Date of cast	Date of test	Age of	Cross	Maximum Load	Compressive	4
No.		· ·	Specimen	section area	(kgf)	Strength	Remarks
			(days)	(cm <sup>2</sup> )		(ksc)	
1	4-Nov-2011	2-Dec-2011	28	16	3,060	191.3	$1 \text{ kgf/cm}^2 = 0.0981 \text{ N/mm}^2$
2	4-Nov-2011	2-Dec-2011	28	16	3,000	187.5	
3	4-Nov-2011	2-Dec-2011	28	16	2,990	186.9	Average compressive strength of
1					Average	188.6	samples = 18.5 N/mm2

Note: This resutls certify the adequacy and representative character of the test samples only.

(Assoc. Prof. Dr. Veerasak Likhitruangsilp)

On Behalf of Head of Civil Engineering Departmen

CHULALONGKORN UNIVERSITY Department of Civil Engineering, Faculty of Engineering

Phayathai Road, Pathumwan, Bangkok 10330 Tel: (662) 218-6567 Fax: (662) 218-6567



Type of test:

SHRINKAGE TEST (EN 12808-4)

Test specimen:

Three (3) specimens in prism shape were cast in the laboratory.

The mix proporting of water to "weber.color power" ratio was 33% by weight.

Client:

SAINT-GOBAIN WEBER CO., LTD.

Date of test:

December 2, 2011

Test results:

The shrinkage of speimens at the age of 28 days are shown as follows.

(The test results are good only for those specimens tested.)

Initial	Final	Drying shrinkage	
Length	Length	of specimen	
(mm)	(mm)	(mm/m)	
163.62	163.40	1.34	
147.07	146.80	1.84	
148.66	148.40	1.75	
	(mm) 163.62 147.07	(mm) (mm) 163.62 163.40 147.07 146.80	

Note: This resutls certify the adequacy and representative character of the test samples only.

(Assoc. Prof. Dr. Veerasak Likhitruangsilp)

On Behalf of Head of Civil Engineering Departmen

Tested by : (Dr. Boonchai Sangpetngam)



Type of test:

WATER ABSORPTION (EN 12808-5)

Test specimen:

Three (3) specimens in prism shape were cast in the laboratory.

The mix proporting of water to "weber.color power" ratio was 33% by weight.

Client:

SAINT-GOBAIN WEBER CO., LTD.

Date of test:

December 2, 2011

Test results:

the water absorption of specimens at the age of 28 days are shown as follows.

(The test results are good only for those specimens tested.)

Specimen	Weight of dry	Weight of	Weight of	Water absorption	Water absorption
No.	specimen	Specimen after	Specimen after	after immersion	after immersion
	(g)	immersion of 30 minimmersion of 240 min		of 30 min	of 240 min
		(g)	(g)	(g)	(g)
1	388.19	390.18	392.73	1.99	4.54
2	363.14	365.16	366.85	2.02	3.71
3	368.29	370.67	371.80	2.38	3.51

Note: This resutls certify the adequacy and representative character of the test samples only.

(Assoc. Prof. Dr. Veerasak Likhitruangsilp)

On Behalf of Head of Civil Engineering Departmen

(Dr. Boonchai Sangpetngam)