

weberdry fleece PE60

Non-woven polyester fleece for using as reinforcement with Weber's Liquid Applied Membrane waterproofing products

- Reinforce the waterproofed areas
- High flexibility for easy application
- Excellent absorption of waterproofing products
- Durable with high strength
- To use with Weber's waterproofing products
 - + weberdry seal
 - + weberdry PUD coat
 - + weberdry PUR seal



Application with Weber's waterproofing products

- Properly clean the substrate until free from any substances that could prevent the adhesion.
- Remove any traces of foreign objects or laitance on substrates to ensure the smoothness before application.
- Prepare the substrates according to each product instruction and prime the substrates with appropriate primers.
 - + weberdry seal + water (1 : 4)
for weberdry seal
 - + weberdry PUD coat + water (9 : 1)
for weberdry PUD coat
 - + weberprim EP 2K
for weberdry PUR seal
- Apply the first layer of waterproofing product. Embed **weberdry fleece PE60** in waterproofing layer.
- Press the fleece well to ensure no bubble or crease.
- Apply the second layer of waterproofing product according to Product Data Sheet until getting the recommended thickness.

weberdry fleece PE60

Material type	Non-woven polyester
Area weight	60 g/m ²
Thickness	0.62 mm
Breaking strength	Machine direction > 140 N/50 mm Cross direction > 120 N/50 mm
Elongation at break	Machine direction > 40% Cross direction > 50%
Width	100 cm ± 1 cm

Size 1 m wide x 50 m long (50 m² per roll)

Weight 60 g/m² (3 kg/roll)

Color white

